

Data sheet
SM 021 (021-1BF00)
Technical data

| | |
|---|-----------------------|
| Order no. | 021-1BF00 |
| Type | SM 021 |
| Module ID | 0005 9FC1 |
| General information | |
| Note | - |
| Features | 8x DI DC 24 V |
| Current consumption/power loss | |
| Current consumption from backplane bus | 65 mA |
| Power loss | 0.9 W |
| Technical data digital inputs | |
| Number of inputs | 8 |
| Cable length, shielded | 1000 m |
| Cable length, unshielded | 600 m |
| Rated load voltage | - |
| Current consumption from load voltage L+ (without load) | - |
| Rated value | DC 20.4...28.8 V |
| Input voltage for signal "0" | DC 0...5 V |
| Input voltage for signal "1" | DC 15...28.8 V |
| Input voltage hysteresis | - |
| Signal logic input | Sinking input |
| Frequency range | - |
| Input resistance | - |
| Input capacitance | - |
| Input current for signal "1" | 3 mA |
| Connection of Two-Wire-BEROs possible | yes |
| Max. permissible BERO quiescent current | 0.5 mA |
| Input delay of "0" to "1" | 3 ms |
| Input delay of "1" to "0" | 3 ms |
| Number of simultaneously utilizable inputs horizontal configuration | 8 |
| Number of simultaneously utilizable inputs vertical configuration | 8 |
| Input characteristic curve | IEC 61131-2, type 1 |
| Initial data size | 8 Bit |
| Status information, alarms, diagnostics | |
| Status display | green LED per channel |
| Interrupts | no |
| Process alarm | no |
| Diagnostic interrupt | no |
| Diagnostic functions | no |
| Diagnostics information read-out | none |
| Module state | green LED |

| | |
|----------------------|---------|
| Module error display | red LED |
|----------------------|---------|

| | |
|-----------------------|------|
| Channel error display | none |
|-----------------------|------|

Isolation

| | |
|------------------|---|
| Between channels | - |
|------------------|---|

| | |
|-------------------------------|---|
| Between channels of groups to | - |
|-------------------------------|---|

| | |
|------------------------------------|-----|
| Between channels and backplane bus | yes |
|------------------------------------|-----|

| | |
|------------------------|----------|
| Insulation tested with | DC 500 V |
|------------------------|----------|

Safety

| | |
|-----------------|---|
| Safety protocol | - |
|-----------------|---|

| | |
|---------------------|---|
| Safety requirements | - |
|---------------------|---|

| | |
|---------------------|---|
| Secure user address | - |
|---------------------|---|

| | |
|----------|---|
| Watchdog | - |
|----------|---|

| | |
|--------------|---|
| Two channels | - |
|--------------|---|

| | |
|--------------------|---|
| Test pulse outputs | - |
|--------------------|---|

Datasizes

| | |
|-------------|---|
| Input bytes | 1 |
|-------------|---|

| | |
|--------------|---|
| Output bytes | 0 |
|--------------|---|

| | |
|-----------------|---|
| Parameter bytes | 0 |
|-----------------|---|

| | |
|------------------|---|
| Diagnostic bytes | 0 |
|------------------|---|

Housing

| | |
|----------|----------------|
| Material | PPE / PPE GF10 |
|----------|----------------|

| | |
|----------|--------------------|
| Mounting | Profile rail 35 mm |
|----------|--------------------|

Mechanical data

| | |
|--------------------|----------------------------|
| Dimensions (WxHxD) | 12.9 mm x 109 mm x 76.5 mm |
|--------------------|----------------------------|

| | |
|------------|------|
| Net weight | 57 g |
|------------|------|

| | |
|------------------------------|------|
| Weight including accessories | 57 g |
|------------------------------|------|

| | |
|--------------|------|
| Gross weight | 71 g |
|--------------|------|

Environmental conditions

| | |
|-----------------------|---------------|
| Operating temperature | 0 °C to 60 °C |
|-----------------------|---------------|

| | |
|---------------------|-----------------|
| Storage temperature | -25 °C to 70 °C |
|---------------------|-----------------|

Certifications

| | |
|------------------|-----|
| UL certification | yes |
|------------------|-----|

| | |
|------------------|-----|
| KC certification | yes |
|------------------|-----|