

**Data sheet**  
**SM 221 (221-1FF40)**
**Technical data**

<b>Order no.</b>	<b>221-1FF40</b>
Type	SM 221
<b>General information</b>	
Note	-
Features	8 inputs AC 230 V Hysteresis
<b>Current consumption/power loss</b>	
Current consumption from backplane bus	60 mA
Power loss	3 W
<b>Technical data digital inputs</b>	
Number of inputs	8
Cable length, shielded	1000 m
Cable length, unshielded	600 m
Rated load voltage	-
Current consumption from load voltage L+ (without load)	-
Rated value	AC 230 V
Input voltage for signal "0"	AC 0...70 V
Input voltage for signal "1"	AC 190...260 V
Input voltage hysteresis	AC 90...160 V
Frequency range	50 Hz
Input resistance	136 kOhm
Input current for signal "1"	-
Connection of Two-Wire-BEROs possible	-
Max. permissible BERO quiescent current	-
Input delay of "0" to "1"	25 ms
Input delay of "1" to "0"	25 ms
Number of simultaneously utilizable inputs horizontal configuration	8
Number of simultaneously utilizable inputs vertical configuration	8
Input characteristic curve	-
Initial data size	1 Byte
<b>Status information, alarms, diagnostics</b>	
Status display	green LED per channel
Interrupts	no
Process alarm	no
Diagnostic interrupt	no
Diagnostic functions	no
Diagnostics information read-out	none
Supply voltage display	none
Group error display	none

Channel error display	none
-----------------------	------

---

**Isolation**

---

Between channels	-
Between channels of groups to	8
Between channels and backplane bus	yes
Insulation tested with	DC 500 V

---

**Datasizes**

---

Input bytes	1
Output bytes	0
Parameter bytes	0
Diagnostic bytes	0

---

**Housing**

---

Material	PPE / PA 6.6
Mounting	Profile rail 35 mm

---

**Mechanical data**

---

Dimensions (WxHxD)	25.4 mm x 76 mm x 88 mm
Net weight	100 g
Weight including accessories	-
Gross weight	-

---

**Environmental conditions**

---

Operating temperature	0 °C to 60 °C
Storage temperature	-25 °C to 70 °C

---

**Certifications**

---

UL certification	yes
KC certification	-