

**Data sheet**  
**SM 222 (222-1BF10)**
**Technical data**

<b>Order no.</b>	<b>222-1BF10</b>
Type	SM 222
<b>General information</b>	
Note	-
Features	8 outputs Output current 2 A
<b>Current consumption/power loss</b>	
Current consumption from backplane bus	70 mA
Power loss	3 W
<b>Technical data digital outputs</b>	
Number of outputs	8
Cable length, shielded	1000 m
Cable length, unshielded	600 m
Rated load voltage	DC 20.4...28.8 V
Current consumption from load voltage L+ (without load)	10 mA
Total current per group, horizontal configuration, 40°C	10 A
Total current per group, horizontal configuration, 60°C	10 A
Total current per group, vertical configuration	10 A
Output current at signal "1", rated value	2 A
Output delay of "0" to "1"	150 µs
Output delay of "1" to "0"	100 µs
Minimum load current	-
Lamp load	5 W
Parallel switching of outputs for redundant control of a load	not possible
Parallel switching of outputs for increased power	not possible
Actuation of digital input	yes
Switching frequency with resistive load	max. 1000 Hz
Switching frequency with inductive load	max. 0.5 Hz
Switching frequency on lamp load	max. 10 Hz
Internal limitation of inductive shut-off voltage	L+ (-52 V)
Short-circuit protection of output	yes, electronic
Trigger level	3 A
Number of operating cycle of relay outputs	-
Switching capacity of contacts	-
Output data size	1 Byte
<b>Status information, alarms, diagnostics</b>	
Status display	green LED per channel
Interrupts	no
Process alarm	no
Diagnostic interrupt	no
Diagnostic functions	no

Diagnostics information read-out	none
Supply voltage display	green LED per group
Group error display	red SF LED
Channel error display	none

### Isolation

Between channels	-
Between channels of groups to	8
Between channels and backplane bus	yes
Insulation tested with	DC 500 V

### Datasizes

Input bytes	0
Output bytes	1
Parameter bytes	0
Diagnostic bytes	0

### Housing

Material	PPE / PA 6.6
Mounting	Profile rail 35 mm

### Mechanical data

Dimensions (WxHxD)	25.4 mm x 76 mm x 88 mm
Net weight	100 g
Weight including accessories	-
Gross weight	-

### Environmental conditions

Operating temperature	0 °C to 60 °C
Storage temperature	-25 °C to 70 °C

### Certifications

UL certification	yes
KC certification	-