

**Data sheet**  
**SM 222 (222-1HF00)**
**Technical data**

<b>Order no.</b>	<b>222-1HF00</b>
Type	SM 222
<b>General information</b>	
Note	-
Features	8x DO DC 30 V AC 230 V 5 A Relay
<b>Current consumption/power loss</b>	
Current consumption from backplane bus	300 mA
Power loss	2 W
<b>Technical data digital outputs</b>	
Number of outputs	8
Cable length, shielded	1000 m
Cable length, unshielded	600 m
Rated load voltage	DC 30 V/ AC 230 V
Current consumption from load voltage L+ (without load)	-
Total current per group, horizontal configuration, 40°C	8 A
Total current per group, horizontal configuration, 60°C	8 A
Total current per group, vertical configuration	8 A
Output current at signal "1", rated value	5 A
Output delay of "0" to "1"	10 ms
Output delay of "1" to "0"	5 ms
Minimum load current	-
Lamp load	-
Parallel switching of outputs for redundant control of a load	not possible
Parallel switching of outputs for increased power	not possible
Actuation of digital input	-
Switching frequency with resistive load	max. 0.33 Hz
Switching frequency with inductive load	max. 0.33 Hz
Switching frequency on lamp load	max. 0.33 Hz
Internal limitation of inductive shut-off voltage	-
Short-circuit protection of output	-
Trigger level	-
Number of operating cycle of relay outputs	10 <sup>7</sup>
Switching capacity of contacts	5 A
Output data size	1 Byte
<b>Status information, alarms, diagnostics</b>	
Status display	green LED per channel
Interrupts	no
Process alarm	no

Diagnostic interrupt	no
Diagnostic functions	no
Diagnostics information read-out	none
Supply voltage display	none
Group error display	none
Channel error display	none

**Isolation**

Between channels	-
Between channels of groups to	-
Between channels and backplane bus	yes
Insulation tested with	DC 500 V

**Datasizes**

Input bytes	0
Output bytes	1
Parameter bytes	0
Diagnostic bytes	0

**Housing**

Material	PPE / PA 6.6
Mounting	Profile rail 35 mm

**Mechanical data**

Dimensions (WxHxD)	25.4 mm x 76 mm x 88 mm
Net weight	110 g
Weight including accessories	-
Gross weight	-

**Environmental conditions**

Operating temperature	0 °C to 60 °C
Storage temperature	-25 °C to 70 °C

**Certifications**

UL certification	yes
KC certification	-