

**Data sheet**  
**SM 231, ECO (231-1BD30)**
**Technical data**

<b>Order no.</b>	<b>231-1BD30</b>
Type	SM 231, ECO
<b>General information</b>	
Note	-
Features	4 inputs Configurable Voltage +/-10 V
<b>Current consumption/power loss</b>	
Current consumption from backplane bus	120 mA
Power loss	0.6 W
<b>Technical data analog inputs</b>	
Number of inputs	4
Cable length, shielded	200 m
Rated load voltage	-
Current consumption from load voltage L+ (without load)	-
Voltage inputs	yes
Min. input resistance (voltage range)	100 kOhm
Input voltage ranges	-10 V ... +10 V
Operational limit of voltage ranges	+/-0.2%
Operational limit of voltage ranges with SFU	-
Basic error limit voltage ranges	+/-0.1%
Basic error limit voltage ranges with SFU	-
Destruction limit voltage	max. 30V
Current inputs	-
Max. input resistance (current range)	-
Input current ranges	-
Operational limit of current ranges	-
Operational limit of current ranges with SFU	-
Grundfehlergrenze Strombereiche	-
Radical error limit current ranges with SFU	-
Destruction limit current inputs (electrical current)	-
Destruction limit current inputs (voltage)	-
Resistance inputs	-
Resistance ranges	-
Operational limit of resistor ranges	-
Operational limit of resistor ranges with SFU	-
Basic error limit	-
Basic error limit with SFU	-
Destruction limit resistance inputs	-
Resistance thermometer inputs	-
Resistance thermometer ranges	-
Operational limit of resistance thermometer ranges	-

Operational limit of resistance thermometer ranges with SFU	-
Basic error limit thermoresistor ranges	-
Basic error limit thermoresistor ranges with SFU	-
Destruction limit resistance thermometer inputs	-
Thermocouple inputs	-
Thermocouple ranges	-
Operational limit of thermocouple ranges	-
Operational limit of thermocouple ranges with SFU	-
Basic error limit thermoelement ranges	-
Basic error limit thermoelement ranges with SFU	-
Destruction limit thermocouple inputs	-
Programmable temperature compensation	-
External temperature compensation	-
Internal temperature compensation	-
Temperature error internal compensation	-
Technical unit of temperature measurement	-
Resolution in bit	13
Measurement principle	successive approximation
Basic conversion time	2 ms / channel
Noise suppression for frequency	f=50 Hz...400 Hz
Initial data size	8 Byte

#### Status information, alarms, diagnostics

Status display	none
Interrupts	no
Process alarm	no
Diagnostic interrupt	no
Diagnostic functions	no
Diagnostics information read-out	none
Supply voltage display	none
Group error display	red SF LED
Channel error display	none

#### Isolation

Between channels	-
Between channels of groups to	-
Between channels and backplane bus	yes
Between channels and power supply	-
Max. potential difference between circuits	-
Max. potential difference between inputs (Ucm)	DC 2 V
Max. potential difference between Mana and Mintern (Uiso)	-
Max. potential difference between inputs and Mana (Ucm)	-
Max. potential difference between inputs and Mintern (Uiso)	DC 75 V/ AC 50 V
Max. potential difference between Mintern and outputs	-
Insulation tested with	DC 500 V

#### Datasizes

Input bytes	8
Output bytes	0
Parameter bytes	12

Diagnostic bytes	0
------------------	---

---

**Housing**

---

Material	PPE / PA 6.6
----------	--------------

---

Mounting	Profile rail 35 mm
----------	--------------------

---

**Mechanical data**

---

Dimensions (WxHxD)	25.4 mm x 76 mm x 88 mm
--------------------	-------------------------

---

Net weight	90 g
------------	------

---

Weight including accessories	-
------------------------------	---

---

Gross weight	-
--------------	---

---

**Environmental conditions**

---

Operating temperature	0 °C to 60 °C
-----------------------	---------------

---

Storage temperature	-25 °C to 70 °C
---------------------	-----------------

---

**Certifications**

---

UL certification	yes
------------------	-----

---

KC certification	-
------------------	---

---