

Data sheet
CM 240, 4port Mini-Switch (240-1DA10)
Technical data

Order no.	240-1DA10
Type	CM 240, 4port Mini-Switch
General information	
Note	-
Features	4 Ports for 10/100 Mbit/s "Plug and play" through Auto-MDI/MDIX-crossover for 100BASE-TX and 10BASE-T LEDs for activity, speed and collision
Current consumption/power loss	
Current consumption from backplane bus	450 mA
Power loss	2 W
Status information, alarms, diagnostics	
Status display	yes
Interrupts	no
Process alarm	no
Diagnostic interrupt	no
Diagnostic functions	no
Diagnostics information read-out	none
Supply voltage display	none
Group error display	none
Channel error display	none
Functionality Sub-D interfaces	
Type	-
Type of interface	-
Connector	-
Electrically isolated	-
MPI	-
MP ² (MPI/RS232)	-
Point-to-point interface	-
5V DC Power supply	-
24V DC Power supply	-
Point-to-point communication	
PtP communication	-
Interface isolated	yes
RS232 interface	-
RS422 interface	-
RS485 interface	-
Connector	RJ45
Transmission speed, min.	10 Mbit/s
Transmission speed, max.	100 Mbit/s
Cable length, max.	-
Point-to-point protocol	
ASCII protocol	-

STX/ETX protocol	-
3964(R) protocol	-
RK512 protocol	-
USS master protocol	-
Modbus master protocol	-
Modbus slave protocol	-
Special protocols	-

Datasizes

Input bytes	-
Output bytes	-
Parameter bytes	-
Diagnostic bytes	-

Housing

Material	PPE / PA 6.6
Mounting	Profile rail 35 mm

Mechanical data

Dimensions (WxHxD)	25.4 mm x 76 mm x 78 mm
Net weight	50 g
Weight including accessories	-
Gross weight	-

Environmental conditions

Operating temperature	0 °C to 60 °C
Storage temperature	-25 °C to 70 °C

Certifications

UL certification	yes
KC certification	-