

Data sheet
 FM 250 (250-1BA00)

Technical data

| | |
|------------------|------------------|
| Order no. | 250-1BA00 |
|------------------|------------------|

| | |
|------|--------|
| Type | FM 250 |
|------|--------|

General information

| | |
|------|---|
| Note | - |
|------|---|

| | |
|----------|---|
| Features | 2/4 channels with 32/16 Bit DC 24 V and above backplane bus 1 A Free configurable Up to 1 MHz |
|----------|---|

Datasizes

| | |
|-------------|----|
| Input bytes | 10 |
|-------------|----|

| | |
|--------------|----|
| Output bytes | 10 |
|--------------|----|

| | |
|-----------------|---|
| Parameter bytes | 4 |
|-----------------|---|

| | |
|------------------|---|
| Diagnostic bytes | 0 |
|------------------|---|

Housing

| | |
|----------|--------------|
| Material | PPE / PA 6.6 |
|----------|--------------|

| | |
|----------|--------------------|
| Mounting | Profile rail 35 mm |
|----------|--------------------|

Mechanical data

| | |
|--------------------|-------------------------|
| Dimensions (WxHxD) | 25.4 mm x 76 mm x 78 mm |
|--------------------|-------------------------|

| | |
|------------|-------|
| Net weight | 230 g |
|------------|-------|

| | |
|------------------------------|---|
| Weight including accessories | - |
|------------------------------|---|

| | |
|--------------|---|
| Gross weight | - |
|--------------|---|

Environmental conditions

| | |
|-----------------------|---------------|
| Operating temperature | 0 °C to 60 °C |
|-----------------------|---------------|

| | |
|---------------------|-----------------|
| Storage temperature | -25 °C to 70 °C |
|---------------------|-----------------|

Certifications

| | |
|------------------|-----|
| UL certification | yes |
|------------------|-----|

| | |
|------------------|---|
| KC certification | - |
|------------------|---|