

Data sheet
 IM 253IBS, INTERBUS slave (253-1IB00)

Technical data

| | |
|--|--|
| Order no. | 253-1IB00 |
| Type | IM 253IBS, INTERBUS slave |
| General information | |
| Note | - |
| Features | INTERBUS slave For 16 input and 16 output modules |
| Technical data power supply | |
| Power supply (rated value) | DC 24 V |
| Power supply (permitted range) | DC 20.4...28.8 V |
| Reverse polarity protection | yes |
| Current consumption (no-load operation) | 50 mA |
| Current consumption (rated value) | 800 mA |
| Inrush current | 60 A |
| I^2t | 0.6 A ² s |
| Max. current drain at backplane bus | 3.5 A |
| Max. current drain load supply | - |
| Power loss | 2 W |
| Status information, alarms, diagnostics | |
| Status display | yes |
| Interrupts | no |
| Process alarm | no |
| Diagnostic interrupt | no |
| Diagnostic functions | no |
| Diagnostics information read-out | none |
| Supply voltage display | green LED |
| Service Indicator | - |
| Group error display | red LED |
| Channel error display | none |
| Hardware configuration | |
| Racks, max. | 1 |
| Modules per rack, max. | 16 |
| Number of digital modules, max. | 16 |
| Number of analog modules, max. | 4 |
| Communication | |
| Fieldbus | INTERBUS-S to DIN 19258 |
| Type of interface | RS422 |
| Connector | Sub-D, 9-pin, male (in) and female (out) |
| Topology | Ring with integrated return line |
| Electrically isolated | yes |
| Number of participants, max. | 256 |

| | |
|-----------------------------|------------|
| Node addresses | - |
| Transmission speed, min. | - |
| Transmission speed, max. | 500 kbit/s |
| Address range inputs, max. | 20 Byte |
| Address range outputs, max. | 20 Byte |
| Number of TxPDOs, max. | - |
| Number of RxPDOs, max. | - |

Housing

| | |
|----------|--------------------|
| Material | PPE / PA 6.6 |
| Mounting | Profile rail 35 mm |

Mechanical data

| | |
|------------------------------|-------------------------|
| Dimensions (WxHxD) | 25.4 mm x 76 mm x 78 mm |
| Net weight | 100 g |
| Weight including accessories | - |
| Gross weight | - |

Environmental conditions

| | |
|-----------------------|-----------------|
| Operating temperature | 0 °C to 60 °C |
| Storage temperature | -25 °C to 70 °C |

Certifications

| | |
|------------------|-----|
| UL certification | yes |
| KC certification | - |