

Data sheet
FM 254 (254-1BA00)
Technical data

Order no.	254-1BA00
------------------	------------------

Type	FM 254
------	--------

General information

Note	-
------	---

Features	For 1-axis drive with servo RS422 Isolated 3x DI, DC 24 V For connecting end switches 2x DO, DC 24 V 1 A
----------	--

Current consumption/power loss

Current consumption from backplane bus	200 mA
--	--------

Power loss	2.5 W
------------	-------

Status information, alarms, diagnostics

Status display	yes
----------------	-----

Interrupts	no
------------	----

Process alarm	no
---------------	----

Diagnostic interrupt	no
----------------------	----

Diagnostic functions	no
----------------------	----

Diagnostics information read-out	none
----------------------------------	------

Supply voltage display	yes
------------------------	-----

Group error display	red LED
---------------------	---------

Channel error display	none
-----------------------	------

Datasizes

Input bytes	16
-------------	----

Output bytes	16
--------------	----

Parameter bytes	18
-----------------	----

Diagnostic bytes	0
------------------	---

Housing

Material	PPE / PA 6.6
----------	--------------

Mounting	Profile rail 35 mm
----------	--------------------

Mechanical data

Dimensions (WxHxD)	25.4 mm x 76 mm x 78 mm
--------------------	-------------------------

Net weight	130 g
------------	-------

Weight including accessories	-
------------------------------	---

Gross weight	-
--------------	---

Environmental conditions

Operating temperature	0 °C to 60 °C
-----------------------	---------------

Storage temperature	-25 °C to 70 °C
---------------------	-----------------

Certifications

UL certification	yes
------------------	-----

