

Data sheet
FM 254 (254-1BA00)
Technical data

| | |
|--|--|
| Order no. | 254-1BA00 |
| Type | FM 254 |
| General information | |
| Note | - |
| Features | Positioning module for 1axis drive with servo For drives with an analog set point interface (+/-10 V control voltage) 3 inputs for connecting end switches and 2 outputs |
| Current consumption/power loss | |
| Current consumption from backplane bus | 200 mA |
| Power loss | 2.5 W |
| Status information, alarms, diagnostics | |
| Status display | yes |
| Interrupts | no |
| Process alarm | no |
| Diagnostic interrupt | no |
| Diagnostic functions | no |
| Diagnostics information read-out | none |
| Supply voltage display | yes |
| Group error display | red LED |
| Channel error display | none |
| Datasizes | |
| Input bytes | 16 |
| Output bytes | 16 |
| Parameter bytes | 18 |
| Diagnostic bytes | 0 |
| Housing | |
| Material | PPE / PA 6.6 |
| Mounting | Profile rail 35 mm |
| Mechanical data | |
| Dimensions (WxHxD) | 25.4 mm x 76 mm x 78 mm |
| Net weight | 130 g |
| Weight including accessories | - |
| Gross weight | - |
| Environmental conditions | |
| Operating temperature | 0 °C to 60 °C |
| Storage temperature | -25 °C to 70 °C |
| Certifications | |
| UL certification | yes |

