

Data sheet

Touch Panel TP 607LC (62H-MGC0-DH)

Technical data

Order no.	62H-MGC0-DH
------------------	--------------------

Type	Touch Panel TP 607LC
------	----------------------

General information

Note	-
------	---

Features	7", TFT, 800x480 pixel Cortex-A8 processor, 667MHz 256 MB work memory, 128 MB user memory RS232, RS422/485, USB-A, Ethernet RJ45 (MPI/DP interface optional available) Windows Embedded CE 6.0 Core, Runtime Movicon CE Basic
----------	---

Display

Display size (diagonal)	7 "
-------------------------	-----

Display size (width)	152 mm
----------------------	--------

Display size (height)	91 mm
-----------------------	-------

Resolution	480 x 800 / 800 x 480
------------	-----------------------

Aspect ratio	5:3
--------------	-----

Type of display	TFT color (64K colors)
-----------------	------------------------

MTBF Backlights (25°C)	50000 h
------------------------	---------

System properties

Processor	Cortex-A8 667 MHz
-----------	-------------------

Operating system	Windows CE 6.0 Core
------------------	---------------------

User software	Movicon 11 CE Basic
---------------	---------------------

Work memory	256 MB
-------------	--------

User memory	128 MB
-------------	--------

Available memory (user data)	40 MB
------------------------------	-------

SD/MMC Slot	yes
-------------	-----

CF Card Slot Typ II	-
---------------------	---

CFast Slot	-
------------	---

Time

Real-time clock buffered	yes
--------------------------	-----

Clock buffered period (min.)	26 w
------------------------------	------

Type of buffering	Manganese Rechargeable Lithium Battery
-------------------	--

Load time for 50% buffering period	5 h
------------------------------------	-----

Load time for 100% buffering period	24 h
-------------------------------------	------

Accuracy (max. deviation per day)	2 s
-----------------------------------	-----

Operating controls

Touchscreen	resistive
-------------	-----------

Touch function	Single Touch
----------------	--------------

Keyboard	external via USB
----------	------------------

Mouse	external via USB
-------	------------------

Interfaces

MPI, PROFIBUS-DP	optional
MPI, PROFIBUS-DP connector	-
Serial, COM1	RS232
COM1 connector	Sub-D, 9-pin, male
Serial, COM2	RS232 / RS422 / RS485
COM2 connector	Sub-D, 25-pin, female
Number of USB-A interfaces	1
USB-A connector	USB-A (host)
Number of USB-B interfaces	-
USB-B connector	-
Number of ethernet interfaces	1
Ethernet	Ethernet 10/100 MBit
Ethernet connector	RJ45
Integrated ethernet switch	-
Video connectors	-
Audio connections	-

Technical data power supply

Power supply (rated value)	DC 24 V
Power supply (permitted range)	DC 20.4...28.8 V
Reverse polarity protection	yes
Current consumption (no-load operation)	0.24 A
Current consumption (rated value)	0.4 A
Inrush current	85 A
I^2t	0.43 A ² s
Power loss	8 W

Status information, alarms, diagnostics

Supply voltage display	none
------------------------	------

Mechanical data

Housing / Protection type

Material	PC
Mounting	mounting clips
Protect type front side	IP 65
Protect type back side	IP 20

Dimensions

Front panel	212 mm x 156 mm x 6 mm
Rear panel	196 mm x 140 mm x 51 mm

Installation cut-out

Width	198 mm
Height	142 mm
Minimum	2.5 mm
Maximum front panel thickness	6 mm
Net weight	1200 g

Environmental conditions

Operating temperature	0 °C to 50 °C
-----------------------	---------------

Storage temperature -20 °C to 60 °C

Certifications

UL certification yes

KC certification -
