

Data sheet
VIPA Touch Panel TP 610C RFID (62K-JIDR-CX)
Technical data

Order no.	62K-JIDR-CX
Type	VIPA Touch Panel TP 610C RFID
General information	
Note	-
Features	Display: 10,4" Processor: XScale-CPU 1066 MHz RAM [MB]: 256 User memory [MB]: 512 External slot: SD Card CF Card Onboard Interface: 1x RS232 1x 422/485 2x USB-A 1x USB-B 2x RJ45 (Ethernet) 1x MPI/PROFIBUS-DP Software: CE6.0 Professional
Display	
Display size (diagonal)	10.4 "
Display size (width)	211.2 mm
Display size (height)	158.4 mm
Resolution	600 x 800 / 800 x 600
Aspect ratio	4:3
Type of display	TFT color (16.7M colors)
MTBF Backlights (25°C)	50000 h
System properties	
Processor	Xscale 1.1 GHz
Operating system	Windows CE 6.0 Prof.
User software	-
Work memory	256 MB
User memory	512 MB
Available memory (user data)	380 MB
SD/MMC Slot	yes
CF Card Slot Typ II	yes
CFast Slot	-
Time	
Real-time clock buffered	yes
Clock buffered period (min.)	6 w
Type of buffering	Vanadium Rechargeable Lithium Battery
Load time for 50% buffering period	10 h
Load time for 100% buffering period	48 h
Accuracy (max. deviation per day)	10 s
Operating controls	
Touchscreen	resistive
Touch function	Single Touch
Keyboard	external via USB
Mouse	external via USB
Interfaces	
MPI, PROFIBUS-DP	RS485 isolated

MPI, PROFIBUS-DP connector	Sub-D, 9-pin, female
Serial, COM1	RS232
COM1 connector	Sub-D, 9-pin, male
Serial, COM2	RS422/485 isolated
COM2 connector	Sub-D, 9-pin, female
Number of USB-A interfaces	2
USB-A connector	USB-A (host)
Number of USB-B interfaces	1
USB-B connector	USB-B (device)
Number of ethernet interfaces	2
Ethernet	Ethernet 10/100 MBit
Ethernet connector	RJ45
Integrated ethernet switch	yes
Video connectors	-
Audio connections	-

Technical data power supply

Power supply (rated value)	DC 24 V
Power supply (permitted range)	DC 20.4...28.8 V
Reverse polarity protection	yes
Current consumption (no-load operation)	0.51 A
Current consumption (rated value)	0.7 A
Inrush current	7 A
$I_{\Delta t}$	0.25 A²s
Power loss	12.2 W

Status information, alarms, diagnostics

Supply voltage display	yes
------------------------	-----

Mechanical data

Housing / Protection class

Material	die-cast aluminum
Mounting	via integrated pivoted lever
Protection class IP front side	IP 65
Protection class IP back side	IP 20
Protection class NEMA front side	-
Protection class NEMA back side	-

Dimensions

Front panel	304 mm x 233 mm x 7.5 mm
Rear panel	285 mm x 215 mm x 45 mm

Installation cut-out

Width	287 mm
Height	217 mm
Minimum	1.5 mm
Maximum front panel thickness	6 mm
Net weight	3251 g
Weight including accessories	-
Gross weight	-

Environmental conditions

Operating temperature	0 °C to 50 °C
-----------------------	---------------

Storage temperature	-20 °C to 60 °C
---------------------	-----------------

Certifications

UL certification	-
------------------	---

KC certification	-
------------------	---
