

**Data sheet**

VIPA TM-C VPN Router WAN/LAN/MPI (900-2C610)

## Technical data

<b>Order no.</b>	<b>900-2C610</b>
Type	VIPA TM-C VPN Router WAN/LAN/MPI
<b>General information</b>	
Note	-
Features	For remote access via Talk2M VPN 4x RJ45 LAN 100 Mbit/s (integrated switch, 1x configurable LAN/WAN) 1x SUB-D 9pin MPI/PROFIBUS up to 12 Mbit/s 1x digital input and output
<b>Inputs and outputs</b>	
Inputs	1 DI: 0/24 V DC, isolated
Outputs	1 DO: open drain, max. 200 mA at DC 30 V
<b>Communication</b>	
serial port	MPI/PROFIBUS, isolated, up to 12 MBit/s
LAN	4 x RJ45, 10/100 MBit/s Switch
WAN	1 x RJ45, 10/100 MBit/s
Modem type	-
<b>Router</b>	
Router functions	Talk2M
RAS	-
<b>VPN</b>	
VPN mode	-
Talk2M	yes
Gateway protocols	-
<b>Services</b>	
Server services	FTP HTTP
Client Services	-
<b>Data management</b>	
Custom Website	yes
Project	web interface
Integrated protocols	-
<b>Interrupts</b>	
Alarm message	-
Alarm	-
<b>Housing</b>	
Material	-
Mounting	Profile rail 35 mm
<b>Mechanical data</b>	
Dimensions (WxHxD)	39 mm x 129 mm x 108 mm
Net weight	410 g

Weight including accessories	-
Gross weight	-
<b>Environmental conditions</b>	
Operating temperature	-20 °C to 70 °C
Storage temperature	-25 °C to 70 °C
<b>Certifications</b>	
UL certification	-
KC certification	-