

Data sheet

VIPA TM-H VPN Router WAN/LAN/MPI (900-2H611)

Technical data

Order no.	900-2H611
Type	VIPA TM-H VPN Router WAN/LAN/MPI
General information	
Note	-
Features	For remote access via Talk2M VPN 4x RJ45 LAN 100Mbit/s (integrated switch, 1 extra WAN Port) 1x RJ45 WAN 100 Mbit/s 1x SUB-D 9pin MPI/PROFIBUS up to 12 Mbit/s 1x digital input and output Alarm management
Inputs and outputs	
Inputs	1 DI: 0/24 V DC, isolated
Outputs	1 DO: open drain, max. 200 mA at DC 30 V
Communication	
serial port	MPI/PROFIBUS, isolated, up to 12 MBit/s
LAN	4 x RJ45, 10/100 MBit/s Switch
WAN	1 x RJ45, 10/100 MBit/s
Modem type	-
Router	
Router functions	IP-Forwarding IP-Filter NAT Port-Forwarding Routing Table DHCP-Client
RAS	PPP Dial-In PPP Dial-Out Call-Back
VPN	
VPN mode	Open VPN 2.0, Client/Server
Talk2M	yes
Gateway protocols	MPI PPI PROFIBUS ISO TCP Modbus TCP
Services	
Server services	FTP HTTP
Client Services	FTP SMTP NTP DYNDNS SNMP
Data management	
Custom Website	yes
Project	web interface
Integrated protocols	MPI PPI PROFIBUS ISO TCP Modbus TCP

Interrupts

Alarm message	E M a i l S M S S N M P F T P
Alarm	E M a i l H a r d w a r e I O S M S P L C - v a r i a b l e s S N M P s y s t e m v a r i a b l e s F T P

Housing

Material	-
Mounting	Profile rail 35 mm

Mechanical data

Dimensions (WxHxD)	39 mm x 129 mm x 108 mm
Net weight	410 g
Weight including accessories	-
Gross weight	-

Environmental conditions

Operating temperature	-20 °C to 70 °C
Storage temperature	-25 °C to 70 °C

Certifications

UL certification	-
KC certification	-